

Cell instance segmentation with deep learning using sparse annotations

K. Sugawara^{1,2,3}, M. Averof^{2,3}

¹ RIKEN Center for Biosystems Dynamics Research, Kobe, Japan; ² Institut de Génomique Fonctionnelle de Lyon (IGFL), Lyon, France; ³ Centre National de la Recherche Scientifique (CNRS), Paris, France.

Abstract

Cell image segmentation is an essential step in many bioimage analyses and a number of deep learning-based algorithms have been developed. These algorithms perform well when a suitable model is selected and trained with a sufficient amount of data. However, collecting large amounts of annotated data remains a major challenge. Here, we demonstrate that training on a few sparsely annotated data can yield effective deep learning models. We further illustrate that the selection of cells to be annotated has a substantial impact on performance. In this work, StarDist [1] and Cellpose [2], which are widely used tools in cell instance segmentation, were adapted to sparsely annotated data and evaluated in conjunction with ELEPHANT [3], a cell tracking algorithm that internally uses the cell segmentation algorithm. Our results suggest that deep learning with sparse annotation is a commonly effective strategy for cell instance segmentation.

References

1. Schmidt, U., Weigert, M., Broaddus, C., & Myers, G. (2018). Cell Detection with Star-convex Polygons. *International Conference on Medical Image Computing and Computer-Assisted Intervention (MICCAI)*.
2. Stringer, C., Wang, T., Michaelos, M., & Pachitariu, M. (2021). Cellpose: a generalist algorithm for cellular segmentation. *Nature methods*, *18*(1), 100-106.
3. Sugawara, K., Çevrim, Ç., & Averof, M. (2022) Tracking cell lineages in 3D by incremental deep learning. *eLife* **11**:e69380.